

CANADIAN PRECAST CONCRETE QUALITY ASSURANCE (CPCQA) CERTIFICATION PROGRAM

SCHEDULE A

Page 1 of 2

THIS SCHEDULE lists the precast concrete products of

Porters Infrastructure Products Inc.
10357 Base Line
Dresden, Ontario
NOP 1M0

That have been found to comply with the **Canadian Precast Concrete Quality Assurance (CPCQA) Certification Program** with respect to the precast concrete products on the subsequent pages of this schedule.

This plant and manufactured products are subject to periodic inspection and testing by the Accredited Certification Organization, (ACO) of the CPCQA Program. Failure on the part of **Porters Infrastructure Products Inc.** to maintain the required quality control or comply with all prequalification requirements or failure of the product manufactured at the said plant to comply with the standard specifications may, at the discretion of the CPCQA Quality Assurance Council, (QAC) result in revision of this plant's Program compliance with respect to any or all precast products listed in this schedule.

The CPCQA does not represent that all product of the type referred to herein made by the Certificate Holder will meet the required standards, only that the Certificate Holder can make compliant product. It is the responsibility of the Contractors or others who acquire product made by the Certificate Holder to ensure that such product meets requirements satisfactory for its use.

Except as provided for above, this Schedule is valid to **January 31, 2024**, for the following products:

CANADIAN PRECAST CONCRETE QUALITY ASSURANCE (CPCQA) CERTIFICATION PROGRAM

Page 2 of 2

<u>CIRCULAR MANHOLES</u>	<u>Joint</u>	<u>Standard or Specification</u>
1200, 1500, 1800, 2400 mm	Single Offset Self-Lubricating Gasket	CSA A257.4

All related products: base slabs, mono bases, flat caps, transitions, risers.

<u>CATCH BASINS</u>	<u>Standard or Specification</u>
600 x 600 mm (115 mm wall) Single Catch Basin 600 x 600 mm (150 mm wall) Single Catch Basin 600 x 1450 mm (115 mm wall) Double Catch Basin 600 x 600 mm (150 mm wall) Ditch Inlet 600 x 1200 mm (150 mm wall) Ditch Inlet 1200 x 1200 mm (225 mm wall) Ditch Inlet	CSA A257.4

<u>PIPE HEADWALLS</u>	<u>Standard or Specification</u>
2835 x 1675 mm to 4695 x 2120 mm	OPSD 804.03 OPSD 804.04

<u>REINFORCED CONCRETE BOX CULVERT</u>	<u>Standard or Specification</u>
1800 x 900 mm to 3000 x 2400 mm	OPSS 1821

All related products: fittings, bends, reducers, increasers, beveled ends, sloped ends, plugs, caps, and radius boxes.