

CANADIAN PRECAST CONCRETE QUALITY ASSURANCE (CPCQA) CERTIFICATION PROGRAM

SCHEDULE A

Page 1 of 3

THIS SCHEDULE lists the precast concrete products of

DECAST Ltd.
8807 Simcoe Road #56
Utopia, Ontario
LOM 1T0

That have been found to comply with the **Prequalification Requirements for Precast Concrete Drainage Products**, (Revised February 2016) as certified by the **Canadian Precast Concrete Quality Assurance (CPCQA) Certification Program** with respect to the precast concrete product on pages 2 and 3 of this schedule.

This plant and its output of products are subject to periodic inspection and testing by the engineer. Failure on the part of **DECAST Ltd.** to maintain the required quality control or comply with all prequalification requirements or failure of the product manufactured at the said plant to comply with the standard specifications may, at the discretion of the CPCQA Quality Assurance Council, result in the decertification of this plant with respect to any or all precast products listed in this schedule.

The CPCQA does not represent that all product of the type referred to herein made by the Certificate Holder will meet the required standards, only that the Certificate Holder is capable of making such product. It is the responsibility of the Contractors or others who acquire product made by the Certificate Holder to ensure that such product meets requirements satisfactory for its use.

Except as provided for above, this Schedule is valid to **January 31, 2022** for the following products:

CANADIAN PRECAST CONCRETE QUALITY ASSURANCE (CPCQA) CERTIFICATION PROGRAM

Page 2 of 3

CONCRETE PIPE

<u>CIRCULAR PIPE</u>	<u>Joint</u>	<u>Governing Specification</u>
450 to 2700 mm	Single Offset Self-Lubricating Gasket	CSA A257.2 (Reinforced) Classes 65D, 100D, 140D
3000 mm		Classes 50D, 65D, 100D, 140D

All related products, fittings, bends, reducers, increasers, plugs, caps, and radius pipe.

<u>MICROTUNNELING PIPE</u>	<u>Joint</u>	<u>Governing Specification</u>
600 to 2700 mm Microtunneling	Single Offset Self-Lubricating Gasket	CSA A257.2 (Reinforced) Classes 65D, 100D, 140D AWWA C302
1050 mm Microtunneling	Single Offset Self-Lubricating Gasket	CSA A257.2 (Reinforced) Class 180D AWWA C302

All related products, fittings, bends, reducers, increasers, plugs, caps, and radius pipe.

MANHOLES (MAINTENANCE HOLES)

<u>MANHOLES (Circular)</u>	<u>Joint</u>	<u>Governing Specification</u>
1200 to 3600 mm	Single Offset	CSA A257.4
1200 mm IFC Taper Top	Self-Lubricating Gasket	

All related products: base slabs, flat caps, transitions, risers, monolithic bases, tapered tops, drop connections, pre-benching, and grade rings.

CANADIAN PRECAST CONCRETE QUALITY ASSURANCE (CPCQA) CERTIFICATION PROGRAM

Page 3 of 3

CATCH BASINS

Governing Specification

600 x 600 mm (115 mm wall) Single Catch Basin
1450 x 600 mm Double Catch Basin
600 x 600 mm (150 mm wall) Ditch Inlet
1200 x 600 mm (150 mm wall) Ditch Inlet

CSA A257.4

STRUCTURAL UNITS

REINFORCED CONCRETE BOX CULVERT

Governing Specifications

1800 x 1200 to 3000 x 2400 mm

OPSS 1821

All related products: fittings, bends, reducers, increasers, plugs, caps, and radius boxes

HEADWALLS

Governing Specifications

2835 x 1675 to 4695 x 2120 mm

OPSD 804.03
OPSD 804.04

BRIDGE SECTIONS

Governing Specifications

Short Span Bridge Sections
3600 x 1800 mm to 16,000 x 3660 mm

CSA A23.4
Category B1

STRUCTURAL DRAINAGE PRODUCTS

Governing Specifications

Box Sections
900 x 900 to 7500 x 4000 mm

CSA A23.4
Category D1

Ver.1-2022