

CANADIAN PRECAST CONCRETE QUALITY ASSURANCE (CPCQA) CERTIFICATION PROGRAM

SCHEDULE A

Page 1 of 3

THIS SCHEDULE lists the precast concrete products of

DECAST Ltd.
8807 Simcoe Road #56
Utopia, Ontario
LOM 1T0

That have been found to comply with the **Canadian Precast Concrete Quality Assurance (CPCQA) Certification Program** with respect to the precast concrete products on the subsequent pages of this schedule.

This plant and manufactured products are subject to periodic inspection and testing by the Accredited Certification Organization, (ACO) of the CPCQA Program. Failure on the part of **DECAST Ltd.** to maintain the required quality control or comply with all prequalification requirements or failure of the product manufactured at the said plant to comply with the standard specifications may, at the discretion of the CPCQA Quality Assurance Council, (QAC) result in revision of this plant's Program compliance with respect to any or all precast products listed in this schedule.

The CPCQA does not represent that all product of the type referred to herein made by the Certificate Holder will meet the required standards, only that the Certificate Holder can make compliant product. It is the responsibility of the Contractors or others who acquire product made by the Certificate Holder to ensure that such product meets requirements satisfactory for its use.

Except as provided for above, this Schedule is valid to **January 31, 2024**, for the following products:

CANADIAN PRECAST CONCRETE QUALITY ASSURANCE (CPCQA) CERTIFICATION PROGRAM

Page 2 of 3

CIRCULAR PIPE	Joint	Standard or Specification
450 to 3000 mm	Single Offset Self-Lubricating Gasket	CSA A257.2 (Reinforced) All Classes
600 to 2700 mm Microtunneling	Single Offset Self-Lubricating Gasket AWWA C302	CSA A257.2 (Reinforced) All Classes

All related products, fittings, bends, reducers, increasers, flared ends, plugs, caps, and radius pipe.

CIRCULAR MANHOLES	Joint	Standard or Specification
1200 to 3600 mm 1200 mm IFC Taper Top	Single Offset Self-Lubricating Gasket	CSA A257.4

All related products: base slabs, flat caps, transitions, risers, monolithic bases, tapered tops, drop connections, pre-benching, and grade rings.

CATCH BASINS	Standard or Specification
600 x 600 mm (115 mm wall) Single Catch Basin 1450 x 600 mm Double Catch Basin 600 x 600 mm (150 mm wall) Ditch Inlet 1200 x 600 mm (150 mm wall) Ditch Inlet	CSA A257.4

REINFORCED CONCRETE BOX CULVERT	Standard or Specification
1800 x 900 to 3000 x 2400 mm	OPSS 1821

All related products: fittings, bends, reducers, increasers, beveled ends, sloped ends, plugs, caps, and radius boxes.

CANADIAN PRECAST CONCRETE QUALITY ASSURANCE (CPCQA) CERTIFICATION PROGRAM

Page 3 of 3

HEADWALLS	Standard or Specification
2835 x 1675 to 4695 x 2120 mm	OPSD 804.03 OPSD 804.04
STRUCTURAL PRECAST CONCRETE PRODUCTS	Standard or Specification
Precast Bridge Products	CSA A23.4 Group B, Category B4
Precast Concrete Drainage Products	CSA A23.4 Group D, Category D1