

# CANADIAN PRECAST CONCRETE QUALITY ASSURANCE (CPCQA) CERTIFICATION PROGRAM

## SCHEDULE A

Page 1 of 2

THIS SCHEDULE lists the precast concrete products of

***Miller Precast Limited***  
***58 Cooper Road***  
***Rossllyn, ON***  
***P7K 0E3***

That have been found to comply with the **Prequalification Requirements for Precast Concrete Drainage Products**, (Revised February 2016) as certified by the **Canadian Precast Concrete Quality Assurance (CPCQA) Certification Program** with respect to the precast concrete product on page 2 of this schedule.

This plant and its output of product are subject to periodic inspection and testing by the Accredited Certification Organization, (ACO). Failure on the part of **Miller Precast Ltd.** to maintain the required quality control or comply with all prequalification requirements or failure of the product manufactured at the said plant to comply with the standard specifications may, at the discretion of the CPCQA Quality Assurance Council, result in the decertification of this plant with respect to any or all precast products listed in this schedule.

The CPCQA does not represent that all product of the type referred to herein made by the Certificate Holder will meet the required standards, only that the Certificate Holder is capable of making such product. It is the responsibility of the Contractors or others who acquire product made by the Certificate Holder to ensure that such product meets requirements satisfactory for its use.

Except as provided for above, this Schedule is valid to **January 31, 2022** for the following products:

# CANADIAN PRECAST CONCRETE QUALITY ASSURANCE (CPCQA) CERTIFICATION PROGRAM

Page 2 of 2

## **MANHOLES (MAINTENANCE HOLES)**

<b><u>CIRCULAR MANHOLES</u></b>	<b><u>Joint</u></b>	<b><u>Governing Specification</u></b>
1200-3000 mm diameter	Single Offset Self-Lubricating Gasket	CSA A257.4 OPSS 1351

All related products: base slabs, flat caps, transitions, risers, monolithic bases, tapered tops, drop connections, pre-benching and grade rings.

<b><u>CATCH BASINS</u></b>	<b><u>Governing Specification</u></b>
600 x 600 mm (115 mm wall) Single Catch Basin 600 x 600 mm (150 mm wall) Single Catch Basin 840 x 600 mm (115 mm wall) Curb Inlet 1450 x 600 mm Double Catch Basin 600 x 600 mm (150 mm wall) Ditch Inlet 1200 x 600 mm (150 mm wall) Ditch Inlet Catch basin (Precast Barrel Type) Catch basin (Inlet)	CSA A257.4      Thunder Bay - STD S-107 Thunder Bay – STD S-108

## **STRUCTURAL UNITS**

<b><u>REINFORCED CONCRETE BOX CULVERT</u></b>	<b><u>Governing Specifications</u></b>
1800 x 1200 mm to 3000 x 2400 mm	OPSS 1821

All related products: fittings, bends, reducers, increasers, plugs, caps, and radius boxes

<b><u>REINFORCED CONCRETE END WALLS AND HEAD WALLS</u></b>	<b><u>Governing Specifications</u></b>
2835 x 1675 mm to 4695 x 2120 mm	OPSD 804.03 & 804.04

Ver.1-2022